

Serial No. 09/548,213

REMARKS

In accordance with the foregoing, the specification and claims 101, 105, 109, 118, 122, 126, 172, 176, 184, 185, 190 and 195 have been amended. Claims 103, 106, 111, 120, 124, 128, 173, 177, 187, 192, and 197 have been cancelled. Claims 1-10, 102, 104, 105, 107-110, 112, 118 119, 121-123, 125-127, 129, 148-172, 174-176, 178-186, 188-191, 193-196 and 198-199 are pending and under consideration.

In item 1, the Examiner indicates that a Supplemental Oath/Declaration must be filed before the application can be allowed. As discussed below, claim amendments are being presented herewith. Because most, if not all, claim changes add subject matter, it is believed that they do not change the allowable status. However, to avoid unnecessary declarations, applicants await confirmation from the Examiner that all claims are allowed.

With regard to item 2, the Examiner requests that the specification be amended to indicate that more than one Reissue Application has been filed. This change has been made.

In item 3, the Examiner objects to claims 101-112, 118-129 and 148-199 because they are not underlined. Two versions of the claims are being presented herewith. In the body of this amendment, all claims after the last patent claim are underlined in their entirety. However, it is believed that this format could be difficult for the Examiner to review. Accordingly, the claims in the attached Claim Appendix include markings to indicate the changes that have been made relative to the immediately prior version of the claims.

MPEP§ 1453 and 37.CFR § 1.173 indicate that all changes must be made relative to the patent and that all pending claims must be numbered consecutively from the last patented claim. On the other hand, MPEP § 1453 also indicates that the claims are not to be renumbered. Applicants agree that claim renumbering is not desirable. To avoid confusion, in the claim amendments presented in the body of this amendment, every claim after the last patented claim, which is not currently under consideration, is shown with the indicator "withdrawn." It is believed this indicator is consistent with avoiding renumbering of the claims. On the other hand, in the Claim Appendix, claims after the last patented claim, which are not currently under consideration, are shown with the indicator "cancelled." This indicator more accurately describes the status of these claims. For example, in the body of the amendment claims 11-100 are shown as being "withdrawn." On the other hand, in the claim appendix claims 11-100 are shown as being "cancelled."

Serial No. 09/548,213

MPEP § 1453 (V) (C) indicates that the Examiner will renumber any remaining claims in numerical order. Accordingly, it is respectfully requested that the Examiner attend to renumbering the claims before the patent is reissued.

Antecedent basis for the claim changes can be found as follows:

<u>Amended Claims</u>	<u>Antecedent Basis</u>
101	Previous claim 103
105	Previous claim 106
109	Previous claim 111
118	Previous claim 120
122	Previous claim 124
126	Previous claim 128
172	Previous claim 173
176	Previous claim 177
183	Previous claim 184
184	Current claim 183
185	Previous claim 187
190	Previous claim 192
195	Previous claim 197

In accordance with the foregoing, it is submitted that the objections raised in the Office Action have been addressed and that the claim amendments do not change the allowable nature of the claims. The Examiner is respectfully requested to confirm that all claims are in condition for allowance. At that time, a supplemental reissue oath/declaration will be promptly prepared.

There being no further outstanding objections or rejections, it is submitted that the application is in condition for allowance. An early action to that effect is courteously solicited.

Serial No. 09/548,213

Finally, if there are any formal matters remaining after this response, the Examiner is requested to telephone the undersigned to attend to these matters.

If there are any additional fees associated with filing of this Amendment, please charge the same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY LLP

Date: June 4 2007By: Mark J. Henry
Registration No. 36,162

1201 New York Avenue, NW, 7th Floor
Washington, D.C. 20005
Telephone: (202) 434-1500
Facsimile: (202) 434-1501

CERTIFICATE OF FACSIMILE TRANSMISSION

I hereby certify that this correspondence is being transmitted via facsimile to: Commissioner for Patents,
P.O. Box 1450, Alexandria, VA 22313-1450
on June 4, 2007
STAAS & HALSEY Diana F. Hill
By: Diana F. Hill
Date: June 4, 2007

Appendix to Amendment

1. (Original) A system for controlling the supply of power from an external power source to rechargeable batteries in an apparatus which can be powered either by the external power source or the rechargeable batteries, comprising:

a first detector for detecting a difference between a maximum permissible charging current allowed by the rechargeable batteries and a charging current flowing to the rechargeable batteries;

a second detector for detecting a maximum useable current by detecting a difference between a maximum suppliable current allowed by the external power source and the current being consumed by the apparatus;

a third detector for detecting a difference between the maximum useable current and the charging current flowing to the rechargeable batteries; and

a controller for controlling power supplied from the external power source to the rechargeable batteries in accordance with the differences detected by the first and third detectors so that the charging current flowing to the rechargeable batteries does not exceed the maximum permissible charging current and does not exceed the maximum useable current.

2. (Original) A system for controlling as set forth in claim 1, further comprising a fourth detector for detecting a difference between a maximum permissible supply voltage allowed by said rechargeable batteries and a voltage applied to said rechargeable batteries, said control means controlling the power supplied from the external power source to the rechargeable batteries in accordance with the difference detected by the fourth detector so that the voltage applied to the rechargeable batteries does not exceed the maximum permissible supply voltage.

3. (Original) A system for controlling the supply of power from an external power source to rechargeable batteries in an apparatus which can be powered by either the external power source or the rechargeable batteries, comprising:

a first detector for detecting a difference between a maximum permissible charging current allowed by the rechargeable batteries and a charging current flowing to the rechargeable batteries;

a second detector for detecting a difference between a lowest permissible output voltage allowed by the external power source and an output voltage which is being output by the external power source; and

a controller for controlling power supplied from the external power source to the

rechargeable batteries in accordance with the differences detected by the first and second detectors so that the charging current flowing to the rechargeable batteries does not exceed the maximum permissible charging current and the output voltage being output by the external power source is not less than the lowest permissible output voltage.

4. (Original) A control system for controlling as set forth in claim 3, further comprising a third detector for detecting a difference between the maximum permissible supply voltage allowed by the rechargeable batteries and a voltage applied to said rechargeable batteries, said control means controlling the power supplied from the external power source to the rechargeable batteries in accordance with the difference detected by the third detector so that the voltage applied to the rechargeable batteries does not exceed the maximum permissible supply voltage.

5. (Original) A system for controlling as set forth in claim 1, wherein said controller controls the power supplied from the external power source to the rechargeable batteries by determining if either the first or third detector detects a negative difference thus indicating that the charging current exceeds a maximum, wherein if either of the first or third detector detects a negative difference, the controller selects the largest negative difference and controls the charging current to increase the largest negative difference to a zero difference, and wherein if neither of the first or third detector detects a negative difference, the controller selects the largest positive difference and controls the charging current to decrease the largest positive difference to a zero difference.

6. (Original) A system for controlling as set forth in claim 2, wherein said controller controls the power supplied from the external power source to the rechargeable batteries by determining if any of the first, third or fourth detector detects a negative difference thus indicating that the charging current or the supply voltage exceeds a maximum,

wherein if any of the first, third or fourth detector detects a negative difference, the controller selects the largest negative difference and controls the charging current to increase the largest negative difference to a zero difference, and

wherein if none of the first, third or fourth detector detects a negative difference, the controller selects the largest positive difference and controls the charging current to decrease the largest positive difference to a zero difference.

7. (Original) A system for controlling as set forth in claim 3,

wherein said controller controls the power supplied from the external power source to the rechargeable batteries by determining if either of the detectors detects a negative difference thus indicating that the charging current exceeds a maximum or the output voltage is less than a minimum,

wherein if either of the detectors detects a negative difference, the controller selects the largest negative difference and controls the charging current to increase the largest negative difference to a zero difference, and

wherein if neither of the detectors detects a negative difference, the controller selects the largest positive difference and controls the charging current to decrease the largest positive difference to a zero difference.

8. (Original) A system for controlling as set forth in claim 4,

wherein said controller controls the power supplied from the external power source to the rechargeable batteries by determining if any of the detectors detects a negative difference thus indicating that a current or a voltage is greater than a maximum or less than a minimum,

wherein if any of the detectors detects a negative difference, the controller selects the largest negative difference and controls the charging current to increase the largest negative difference to a zero difference, and

wherein if none of the detectors detects a negative difference, the controller selects the largest positive difference and controls the charging current to decrease the largest positive difference to a zero difference.

9. (Original) A system for controlling the supply of power from a charger circuit to rechargeable batteries, the rechargeable batteries being used to supply power to a power supply circuit, comprising:

a sense resistor having two ends, located between the rechargeable batteries and a connection point for the charger circuit and the power supply circuit, the sense resistor detecting current flowing into and out of the rechargeable batteries;

a current measurement device having two inputs connected respectively to the two ends of the sense resistor, the current measurement device determining which of the two inputs has a larger voltage and generating a voltage in accordance with the difference between the voltages of the two inputs to thereby measure the current flowing into or out of the rechargeable battery;

and

a control circuit regulating to a constant current the current flowing into the rechargeable batteries, based on the current flowing into the rechargeable batteries detected by the sense resistor.

10. (Original) A system for controlling as set forth in claim 9, wherein the control circuit has two inputs connected respectively to the two ends of the sense resistor.

11-100. (Cancelled)

101. (Currently Amended) An electronic apparatus having an input section for inputting power from a power source and capable of charging a battery by using the power from the input section while the electronic apparatus makes a load operate by applying the power input from the input section to the load, an output voltage of the power source being substantially a constant voltage, the output voltage of the power source falling to less than said constant voltage when the power source outputs more than a predetermined current value, the power applied to the load from the input section varying based on the state of the load, the electronic apparatus comprising:

a power input sensor for obtaining power-input information by sensing an input of the power from the input section;

a charger for charging the battery by using the power from the input section; and

a charge control circuit for controlling the charging power the charger supplies to the battery based on the power input information obtained by the power input sensor so that a sum of the power applied to the load and the power charged to the battery from the input section is substantially in a current range in which said output voltage of the power source is substantially the constant voltage; and

a charging voltage detector for detecting a charging voltage of the battery, wherein the charge control circuit controls the charging voltage so that the charging voltage detected by the charging voltage detector becomes a value assigned to the battery or lower.

102. (Previously Presented) An electronic apparatus as set forth in claim 101, further comprising:

a charging current detector for detecting a charging current of the battery, wherein the charge control circuit controls the charging current based on the detected charging current so that the charging current becomes a value assigned to the battery or lower.

103. (Cancelled)

104. (Previously Presented) An electronic apparatus as set forth in claim 101, wherein the power source is able to supply a maximum permissible supply current of the power source in the current range.

105. (Currently Amended) A charging apparatus for an electronic apparatus that has an input section for inputting power from a power source and is capable of charging a battery by using the power from the input section while the electronic apparatus makes a load operate by applying the power input from the input section to the load, an output voltage of the power source being substantially a constant voltage, the output voltage of the power source falling to less than said constant voltage when the power source outputs more than a predetermined current value, the power applied to the load from the input section varying based on the state of the load, the charging apparatus comprising:

a charger for charging the battery by using the power from the input section; and

a charge control circuit for controlling the charging power the charger supplies to the battery, based on power input information obtained by a power input sensor for obtaining the power input information by sensing an input of the power from the input section, so that a sum of the power applied to the load and the power charged to the battery from the input section is substantially in a current range in which said output voltage of the power source is substantially the constant voltage, wherein

the charge control circuit controls the charging current, based on a charging current detected by a charging current detector for detecting the charging current of the battery, so that the charging current becomes a value assigned to the battery or lower.

106. (Cancelled)

107. (Previously Presented) A charging apparatus as set forth in claim 105, wherein the charge control circuit further controls the charging voltage so that a voltage detected by a charging voltage detector for detecting the charging voltage of the battery becomes a value assigned to the battery or lower.

108. (Previously Presented) A charging apparatus as set forth in claim 105, wherein the power source is able to supply a maximum permissible supply current of the power source in the current range.

109. (Currently Amended) A charge control circuit for an electronic apparatus that has an input section for inputting power from a power source and a charger for charging a battery by using the power from the input section while the electronic apparatus making a load operate by applying the power input from the input section to the load, an output voltage of the power source being substantially a constant voltage, the output voltage of the power source falling to less than said constant voltage when the power source outputs more than a predetermined current value, the power applied to the load from the input section varying based on the state of the load, the charge control circuit comprising:

a control circuit for controlling the charging power the charger supplies to the battery, based on power input information obtained by a power input sensor for obtaining the power input information by sensing an input of the power from the input section, so that a sum of the power applied to the load and the power charged to the battery from the input section is substantially in a current range in which said output voltage of the power source is substantially the constant voltage, wherein

the control circuit controls the charging voltage so that a voltage detected by a charging voltage detector for detecting the charging voltage of the battery becomes a value assigned to the battery or lower.

110. (Previously Presented) A charge control circuit as set forth in claim 109, wherein the control circuit controls the charging current based a charging current detected by a charging current detector for detecting the charging current of the battery so that the charging current becomes a value assigned to the battery or lower.

111. (Cancelled)

112. (Previously Presented) A charge control circuit as set forth in claim 109, wherein the power source is able to supply a maximum permissible supply current of the power source in the current range.

118. (Currently Amended) An electronic apparatus having an input section for inputting power from a power source and capable of charging a battery by using the power from the input section while making a load operate by applying the power input from the input section to the load, a current applied to the load from the input section varying based on the state of the load,

the electronic apparatus comprising:

a power input sensor which obtains power-input information by sensing an input of the power from the input section;

a charger which charges the battery by using a current from the input section; and

a charge control circuit which controls the charger to change a current charged to the battery by determining whether an input current from the power source reaches a predetermined value or not in accordance with the power-input information sensed by the power input sensor, so that a sum of the current applied to the load and the current charged to the battery from the input section does not exceed the predetermined value; and

a charging voltage detector which detects a charging voltage of the battery, wherein the charge control circuit controls the charging voltage so that the charging voltage detected by the charging voltage detector becomes a value assigned to the battery or lower.

119. (Previously Presented) An electronic apparatus as set forth in claim 118, further comprising:

a charging current detector which detects a charging current of the battery, wherein the charge control circuit controls the charging current based on the detected charging current so that the charging current becomes a value assigned to the battery or lower.

120. (Cancelled)

121. (Previously Presented) An electronic apparatus as set forth in claim 118, wherein the predetermined value is a maximum permissible supply current of the power source.

122. (Currently Amended) A charging apparatus for an electronic apparatus that has an input section for inputting power from a power source and is capable of charging a battery by using the power from the input section while the electronic apparatus making a load operate by applying the power input from the input section to the load, a current applied to the load from the input section varying based on the state of the load, the charging apparatus comprising:

a charger which charges the battery by using the power from the input section; and

a charge control circuit which controls the charger to change a current charged to the battery by determining whether an input current from the power source reaches a predetermined value or not in accordance with the power-input information sensed by a power input sensor which obtains the power input information by sensing an input of power from the input section, so that a sum of the current applied to the load and the current charged to the battery from the input section does not exceed the predetermined value, wherein

the charge control circuit further controls the charging voltage so that a voltage detected by a charging voltage detector for detecting the charging voltage of the battery becomes a value assigned to the battery or lower.

123. (Previously Presented) A charging apparatus as set forth in claim 122, wherein the charge control circuit controls the charging current, based on a charging current detected by a charging current detector for detecting the charging current of the battery, so that the charging current becomes a value assigned to the battery or lower.

124. (Cancelled)

125. (Previously Presented) A charging apparatus as set forth in claim 122, wherein the predetermined value is a maximum permissible supply power of the power source.

126. (Currently Amended) A charge control circuit for an electronic apparatus that has an input section for inputting power from a power source and a charger for charging a battery by using the power from the input section and while the electronic apparatus making a load operate by applying the power input from the input section to the load, a current applied to the load from the input section varying based on the state of the load, the charge control circuit comprising:

a charge control circuit which controls the charger to change a current charged to the battery by determining whether an input current from the power source reaches a predetermined value or not in accordance with the power-input information sensed by a power input sensor which obtains the power input information by sensing an input of power from the input section, so that a sum of the current applied to the load and the current charged to the battery from the input section does not exceed the predetermined value, wherein

the control circuit controls the charging voltage so that a voltage detected by a charging voltage detector for detecting the charging voltage of the battery becomes a value assigned to the battery or lower.

127. (Previously Presented) A charge control circuit as set forth in claim 126, wherein the control circuit controls the charging current based a charging current detected by a charging current detector for detecting the charging current of the battery so that the charging current becomes a value assigned to the battery or lower.

128. (Cancelled)

129. (Previously Presented) A charge control circuit as set forth in claim 126, wherein the predetermined value is a maximum permissible supply power of the power source.

130-147. (Cancelled)

148. (Previously Presented) An electronic apparatus connected to an AC adapter which supplies DC power, capable of charging a battery by using power from the AC adapter while making a load operate by using the DC power supplied from the AC adapter, the power given to the load varying based on the state of the load, the electronic apparatus comprising:

a connector which receives the DC power from the AC adapter;

a charger, connected to the battery, which supplies charging power to the battery by using the power from the connector; and

a charge control circuit which controls the charger to control the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery becomes a value assigned in advance.

149. (Previously Presented) An electronic apparatus as set forth in claim 148, further

comprising a charging current detector which detects a charging current supplied to the battery, wherein the charge control circuit controls the charging current so that the charging current becomes equal to or lower than a value assigned to the battery, based on a value of the charging current to the battery detected by the charging current detector.

150. (Previously Presented) An electronic apparatus as set forth in claim 148, further comprising a charging voltage detector which detects a charging voltage supplied to the battery, wherein the control circuit controls the charging voltage so that the charging voltage becomes equal to or lower than a value assigned to the battery, based on a value of the charging voltage to the battery detected by the charging voltage detector.

151. An electronic apparatus as set forth in claim 148, wherein the value assigned in advance is a maximum permissible supply power of the AC adapter.

152. (Previously Presented) An electronic apparatus as set forth in claim 148, wherein the charge control circuit controls the charging power the charger supplies to the battery, based on sensed information on the power input from the connector, so that a sum of the power applied to the load and the power charged to the battery becomes the value assigned in advance.

153. (Previously Presented) A charging apparatus for charging a battery for an electronic apparatus that is connected to an AC adapter and that is capable of charging the battery by using power from the AC adapter while the electronic apparatus making a load operate by using DC power supplied from the AC adapter, the power given to the load varying based on the state of the load, the charging apparatus comprising:

a charger, connected to the battery, which supplies charging power to the battery by using the power from a connector that is connected to the AC adapter to receive the DC power from the AC adapter; and

a charge control circuit which controls the charger to control the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery becomes a value assigned in advance.

154. (Previously Presented) A charging apparatus as set forth in claim 153, wherein the charge control circuit controls the charging current so that a charging current becomes equal to

or lower than the value assigned to the battery, based on a detected value of the charging current to the battery.

155. (Previously Presented) A charging apparatus as set forth in claim 153, wherein the charge control circuit controls a charging voltage so that the charging voltage becomes equal to or lower than a value assigned to the battery, based on a detected value of the charging voltage to the battery.

156. (Previously Presented) A charging apparatus as set forth in claim 153, wherein the value assigned in advance is a maximum permissible supply power of the AC adapter.

157. (Previously Presented) A charging apparatus as set forth in claim 153, wherein the charge control circuit controls the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery becomes the value assigned in advance, based on sensed information on the power input from the connector.

158. (Previously Presented) A charge control circuit for controlling a charger in an electronic apparatus having a connector connected to an AC adapter to receive DC power from the AC adapter, the charger being connected to a battery and supplying charging power to the battery by using the power from the connector, the electronic apparatus making a load operate by using the DC power supplied from the AC adapter, the power given to the load varying based on the state of the load, the charge control circuit comprising:

a control circuit which controls the charger to control the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery becomes a value assigned in advance.

159. (Previously Presented) A charge control circuit as set forth in claim 158, wherein the control circuit controls a charging current based on a detected value of the charging current to the battery so that the charging current becomes equal to or lower than a value assigned to the battery.

160. (Previously Presented) A charge control circuit as set forth in claim 158, wherein the control circuit controls a charging voltage based on a detected value of the charging voltage to the battery so that the charging voltage becomes equal to or lower than a value assigned to

the battery.

161. (Previously Presented) A charge control circuit as set forth in claim 158, wherein the value assigned in advance is a maximum permissible supply power of the AC adapter.

162. (Previously Presented) A charge control circuit as set forth in claim 158, wherein the control circuit controls the charging power the charger supplies to the battery, based on sensed information on the power input from the connector, so that a sum of the power applied to the load and the power charged to the battery becomes the value assigned in advance.

163. (Previously Presented) An electronic apparatus capable of charging a battery by using power from a power source while making a load operate by using the power supplied from the power source, the electronic apparatus comprising:

- a charger which supplies charging power to the battery by using the power from the power source;

- a detector which detects the power applied to the load;

- a charging current detector detects a charging current to the battery; and

- a control circuit which controls the charger to generate the charging power so that a sum of the charging power supplied to the battery and the power applied to the load that has been detected becomes a value assigned in advance, and which controls the charging current based on the detected charging current so that the charging current to the battery becomes equal to or lower than a charging current value assigned in advance to the battery.

164. (Previously Presented) An electronic apparatus capable of charging a battery by using power from a power source while making a load operate by using the power supplied from the power source, the electronic apparatus comprising:

- a charger which supplies charging power to the battery by using the power from the power source;

- a detector which detects the power applied to the load;

- a charging voltage detector which detects a charging voltage to the battery; and

- a control circuit which controls the charger to generate the charging power so that a sum of the charging power supplied to the battery and the power applied to the load that has been detected becomes a value assigned in advance, and which controls the charging voltage based on the detected charging voltage so that the charging voltage becomes within a voltage value

assigned in advance to the battery.

165. (Previously Presented) An electronic apparatus capable of charging a battery by using power from a power source having a prescribed maximum permissible supply power while making a load operate by using the power supplied from the power source, the electronic apparatus comprising:

- a charger which supplies charging power to the battery by using the power from the power source;

- a detector which detects the power applied to the load; and

- a control circuit which controls the charger to adjust the charger to supply the charging power so that the charging power is the prescribed maximum permissible supply power minus the detected power applied to the load.

166. (Previously Presented) A charging apparatus for an electronic apparatus capable of charging a battery by using power from a power source while the electronic apparatus makes a load operate by using the power supplied from the power source, the charging apparatus comprising:

- a charger which supplies charging power to the battery by using the power from the power source; and

- a control circuit which controls the charger to generate the charging power so that a sum of the charging power supplied to the battery and the power applied to the load detected by a detector which detects the power applied to the load becomes a value assigned in advance, and which controls the charging current, based on a charging current value detected by a charging current detector which detects the charging current to the battery, so that the charging current to the battery becomes equal to or lower than a charging current value assigned in advance to the battery.

167. (Previously Presented) A charging apparatus for an electronic apparatus capable of charging a battery by using power from a power source while the electronic apparatus making a load operate by using the power supplied from the power source, the charging apparatus comprising:

- a charger which supplies charging power to the battery by using the power from the power source;

- and a control circuit which controls the charger to generate the charging power so that a

sum of the charging power supplied to the battery and the power applied to the load detected by a detector which detects the power applied to the load becomes a value assigned in advance, and which controls the charging voltage, based on a charging voltage detected by a charging voltage detector which detects the charging voltage of the battery, so that the charging voltage becomes within a voltage value assigned in advance to the battery.

168. (Previously Presented) A charging apparatus for an electronic apparatus capable of charging a battery by using power from a power source having a prescribed maximum permissible supply power while the electronic apparatus makes a load operate by using the power supplied from the power source, the charging apparatus comprising:

a charger which supplies charging power to the battery by using the power from the power source; and

a control circuit which controls the charger so that the charger supplies the charging power so that the charging power is the maximum permissible supply power minus the power applied to the load that has been detected by a detector which detects the power applied to the load.

169. (Previously Presented) A charge control circuit for controlling a charger for an electronic apparatus that makes a load operate by using power supplied from a power source and that has the charger for supplying charging power to a battery by using the power from the power source, the charge control circuit comprising:

a control circuit which controls the charger to generate the charging power so that a sum of the charging power supplied to the battery and the power applied to the load detected by a detector which detects the power applied to the load becomes a value assigned in advance, and which controls a charging current, based on a charging current detected by a charging current detector which detects the charging current to the battery, so that the charging current supplied to the battery becomes equal to or lower than a charging current value assigned in advance to the battery.

170. (Previously Presented) A charge control circuit for controlling a charger for an electronic apparatus that makes a load operate by using power supplied from a power source and that has the charger for supplying charging power to a battery by using the power from the power source, the charge control circuit comprising:

a control circuit which controls the charger to generate the charging power so that a sum

of the charging power supplied to the battery and the power applied to the load detected by a detector which detects the power applied to the load becomes a value assigned in advance, and which controls the charging voltage, based on a charging voltage detected by a charging voltage detector which detects the charging voltage of the battery, so that the charging voltage becomes within a voltage value assigned in advance to the battery.

171. (Previously Presented) A charge control circuit for controlling a charger for an electronic apparatus that makes a load operate by using power supplied from a power source having a prescribed maximum permissible supply power and that has the charger for supplying charging power to a battery by using the power from the power source, the charge control circuit comprising:

a control circuit which controls the charger so that the charger supplies the charging power which is the prescribed maximum permissible supply power minus the power applied to the load detected by a detector which detects the power applied to the load.

172. (Currently Amended) An electronic apparatus capable of charging a battery by using power from a power source while making a load operate by using the power supplied from the power source, the power applied to the load from the power source varying based on the state of the load, the electronic apparatus comprising:

a charger which supplies charging power to the battery by using the power from the power source;

a charging current detector which detects a charging current to the battery; and

a charge control circuit which controls the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery from the power source becomes a value assigned in advance, and which controls the charging current based on the charging current detected by the charging current detector so that the charging current becomes a limit value assigned to the battery or a lower value; and

a charging voltage detector which detects a charging voltage of the battery, wherein the charge control circuit further controls the charging voltage so that the voltage detected by the charging voltage detector becomes a value assigned to the battery or lower.

173. (Cancelled)

174. (Previously Presented) An electronic apparatus as set forth in claim 172, wherein

the pre-assigned value is a maximum permissible supply power of the power source.

175. (Previously Presented) An electronic apparatus as set forth in claim 172, wherein the charge control circuit controls the charging power the charger supplies to the battery, based on sensed information on the input from the power source, so that a sum of the power applied to the load and the power charged to the battery from the power source becomes the pre-assigned value.

176. (Currently Amended) A charging apparatus for an electronic apparatus that is capable of charging a battery by using power supplied from a power source while the electronic apparatus making a load operate by using the power from the power source, the power applied to the load from the power source varying based on the state of the load, the charging apparatus comprising:

a charger which supplies charging power to the battery by using the power from the power source; and

a charge control circuit which controls the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery from the power source becomes a value assigned in advance, and which controls the charging current, based on a charging current detected by a charging current detector which detects the charging current to the battery, so that the charging current becomes a value assigned to the battery or a lower value, wherein

the charge control circuit further controls the charging voltage so that a charging voltage detected by a charging voltage detector which detects the voltage charged to the battery becomes a value assigned to the battery or lower.

177. (Cancelled)

178. (Previously Presented) A charging apparatus as set forth in 176, wherein the pre-assigned value is a maximum permissible supply power of the power source.

179. (Previously Presented) A charging apparatus as set forth in 176, wherein the charge control circuit controls the charging power the charger supplies to the battery, based on sensed information on the input from the power source, so that a sum of the power applied to the load and the power charged to the battery becomes the pre-assigned value.

180. (Previously Presented) A charge control circuit for an electronic apparatus that makes a load operate by using power supplied from a power source and that has a charger for supplying charging power to a battery by using the power from the power source, the power applied to the load from the power source varying based on the state of the load, the charge control circuit comprising:

a control circuit which controls the charging power the charger supplies to the battery so that a sum of the power applied to the load and the power charged to the battery from the power source becomes a value assigned in advance, and which controls the charging current based on a charging current detected by a charging current detector which detects the charging current to the battery so that the charging current becomes a value assigned to the battery or a lower value.

181. (Previously Presented) A charge control circuit as set forth in claim 180, wherein the control circuit further controls the charging voltage so that a charging voltage detected by a charging voltage detector which detects the voltage charged to the battery becomes a value assigned to the battery or lower.

182. (Previously Presented) A charge control circuit as set forth in 180, wherein the pre-assigned value is a maximum permissible supply power of the power source.

183. (Previously Presented) A charge control circuit as set forth in 180, wherein the control circuit controls the charging power the charger supplies to the battery, based on sensed information on the input from the power source, so that a sum of the power applied to the load and the power from the power source charged from the power source to the battery becomes the pre-assigned value.

184. (Currently Amended) A charge control circuit for an electronic apparatus that has an input section for inputting power from a power source and a charger for charging a battery by using the power from the input section while the electronic apparatus makes a load operate by applying the power input from the input section to the load, an output voltage of the power source being substantially a constant voltage, the output voltage of the power source falling to less than said substantially constant voltage when the power source outputs more than a predetermined current value, the power applied to the load from the input section varying based

on the state of the load, the charge control circuit comprising:

a control circuit which controls the charging power the charger supplies to the battery, based on power input information obtained by a power input sensor which obtains the power input information by sensing an input of the power from the input section, so that a sum of the power applied to the load and the power charged to the battery from the input section is substantially in a current range in which said output voltage of the power source is the substantially constant voltage, wherein the control circuit controls a charging voltage the charger supplies to the battery so that the charging voltage detected by a charging voltage detector becomes a value assigned to the battery or lower, wherein

the control circuit controls the charging power the charger supplies to the battery, based on sensed information on the input from the power source, so that a sum of the power applied to the load and the power from the power source charged from the power source to the battery becomes the pre-assigned value.

185. (Currently Amended) An electronic apparatus connected to an AC adapter which supplies DC current, capable of charging a battery by using current from the AC adapter while making a load operate by using the DC current supplied from the AC adapter, the current given to the load varying based on the state of the load, the electronic apparatus comprising:

a connector connected to the AC adapter, which receives DC current from the AC adapter;

a charger, connected to the battery, which supplies charging current to the battery by using the current from the connector; and

a charger control circuit which controls the charger to control the charging current the charger supplies to the battery so that a sum of the current applied to the load and the current charged to the battery becomes a value assigned in advance; and

a charging voltage detector which detects a charging voltage supplied to the battery, wherein the control circuit controls the charging voltage so that the charging voltage becomes equal to or lower than a value assigned to the battery, based on a value of the charging voltage to the battery detected by the charging voltage detector.

186. (Previously Presented) An electronic apparatus as set forth in claim 185, further comprising a charging current detector which detects a charging current supplied to the battery, wherein the charge control circuit controls the charging current so that the charging current becomes equal to or lower than a value assigned to the battery, based on a value of the charging current to the battery detected by the charging current detector.

187. (Cancelled)

188. (Previously Presented) An electronic apparatus as set forth in claim 185, wherein the value assigned in advance is a maximum permissible supply current of the AC adapter.

189. (Previously Presented) An electronic apparatus as set forth in claim 185, wherein the charge control circuit controls the charging current the charger supplies to the battery, based on sensed information on the power input from the connector, so that a sum of the current applied to the load and the current charged to the battery becomes the value assigned in advance.

190. (Currently Amended) A charging apparatus for charging a battery for an electronic apparatus that is connected to an AC adapter and that is capable of charging the battery by using current from the AC adapter while the electronic apparatus making a load operate by using DC current supplied from the AC adapter, the current given to the load varying based on the state of the load, the charging apparatus comprising:

a charger, connected to the battery, which supplies charging current to the battery by using the current from a connector that is connected to the AC adapter to receive the DC current from the AC adapter; and

a charger control circuit which controls the charger to control the charging current the charger supplies to the battery so that a sum of the current applied to the load and the current charged to the battery becomes a value assigned in advance, wherein

the charge control circuit controls a charging voltage so that the charging voltage becomes equal to or lower than a value assigned to the battery, based on a detected value of the charging voltage to the battery.

191. (Previously Presented) A charging apparatus as set forth in claim 190, wherein the charge control circuit controls the charging current so that a charging current becomes equal to

or lower than the value assigned to the battery, based on a detected value of the charging current to the battery.

192. (Cancelled)

193. (Previously Presented) A charging apparatus as set forth in claim 190, wherein the value assigned in advance is a maximum permissible supply current of the AC adapter.

194. (Previously Presented) A charging apparatus as set forth in claim 190, wherein the charge control circuit controls the charging current the charger supplies to the battery so that a sum of the current applied to the load and the current charged to the battery becomes the value assigned in advance, based on sensed information on input from the connector.

195. (Currently Amended) A charge control circuit for controlling a charger in an electronic apparatus having a connector connected to an AC adapter to receive DC current from the AC adapter, the charger being connected to a battery and supplying charging current to the battery by using the current from the connector, the electronic apparatus making a load operate by using the DC current supplied from the AC adapter, the current given to the load varying based on the state of the load, the charge control circuit comprising:

a control circuit which controls the charger to control the charging current the charger supplies to the battery so that a sum of the current applied to the load and the current charged to the battery becomes a value assigned in advance, wherein

the control circuit controls a charging voltage based on a detected value of the charging voltage to the battery so that the charging voltage becomes equal to or lower than a value assigned to the battery.

196. (Previously Presented) A charge control circuit as set forth in claim 195, wherein the control circuit controls a charging current based on a detected value of the charging current to the battery so that the charging current becomes equal to or lower than a value assigned to the battery.

197. (Cancelled)

198. (Previously Presented) A charge control circuit as set forth in claim 195, wherein the value assigned in advance is a maximum permissible supply current of the AC adapter.

199. (Previously Presented) A charge control circuit as set forth in claim 195, wherein the control circuit controls the charging current the charger supplies to the battery, based on sensed information on input from the connector, so that a sum of the current applied to the load and the current charged to the battery becomes the value assigned in advance.